

# LS4278

## Cordless handheld scanner

### BAR CODE SCANNERS

### Cordless freedom improves productivity and protects profitability

Symbol's cordless LS4278 provides superior bar code scanning in a durable future-proof device that delivers an outstanding total cost of ownership. Workers can move within a 50 ft./15 m radius to scan items — and the elimination of hazardous cables creates a safer work environment. From cashiers moving around the register to scan large, heavy items and check for missed items to healthcare workers double checking that the right patient is receiving the right medication, integrated Bluetooth wireless personal area networking (WPAN) provides reliable and secure wireless transmission of data between the scanner and your host. Productivity is improved, revenues are protected and potential liability due to injury from lifting heavy objects is reduced.

### Outstanding scanning performance

The LS4278 is designed to deliver exceptional scanning performance. Users can scan objects at any angle — the innovative multi-line rastering scan pattern eliminates the need for exact aim and positioning of the scanner. The laser line moves vertically during scanning, allowing accurate capture of even the smallest, stacked and poorly printed bar codes on the first scan. And with superior motion tolerance, users no longer need pause between scans, further increasing productivity.

### A new level of durability — and a lower TCO

The LS4278 scanner and cradle are designed to withstand all day every day use, from drops to spills, with features that deliver maximum uptime and investment protection. The scanner's patented single board construction eliminates the most common point of failure — the interconnection between multiple boards. Even if the scanner is accidentally dropped, a five-foot (1.5m) drop specification ensures continuous reliable operation. The scanner and cradle offer industrial charging contacts that eliminate wear when cradling the device, providing a reliable charging connection through hundreds of thousands of insertions — other common charging techniques show wear between 5,000 to 10,000 insertions. Drain points are designed into the cradle to protect sensitive internal electronics from accidental liquid spills. Built-in enterprise durability combines with Symbol's services to deliver a low total cost of ownership. Symbol's comprehensive services are available to assist in rapid deployment as well as provide the ongoing support you need to maintain peak performance — and achieve maximum uptime and value.

For more information on the LS4278, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at: [www.symbol.com/ls4278](http://www.symbol.com/ls4278)



#### FEATURES

#### BENEFITS

**Bluetooth Class 2 v1.2**

(Serial Port & HID Profiles with authentication and security)

Cordless scanning with secure wireless transmission of data

**Multi-line rastering scan pattern**

Eliminates the need for exact aim and positioning for superior scanning accuracy

**Remote scanner management (RSM) ready**

Discover, provision and upgrade devices from a central remote location; dramatically reduces management effort and costs

**Long life industrial charging contacts**

Reliable performance, rated to 250,000+ insertions

**Patented, single circuit-board**

Lowers TCO by eliminating a major source of vulnerability

**Wide working range**

Reads good and poor quality bar codes at similar ranges, reducing the need for the user to move the scanner back and forth

**Superior motion tolerance**

Eliminates the need to pause between scans

**Withstands 5 ft./1.5 m drops to concrete**

Protects against downtime from breakage due to everyday drops

**Powered through host cable**

Eliminates need for a power supply; simplifies installation

**Plug-and-play; universal cable**

Rapid deployment; single cable connects to any computing environment

**Multi point-to-point**

Use up to three scanners with a single cradle, reducing capital expenditures and maintenance costs

**Batch mode operation**

Increases application design flexibility to better meet your specific needs

**Vertical or horizontal mounting**

Provides versatility to accommodate your unique environment

# LS4278 Specifications

## Physical Characteristics

Dimensions:	Scanner: 7.3 in. H x 3.85 in. L x 2.7 in. W/ 18.5 cm H x 9.7 cm L x 6.9 cm W Cradle: 2.0 in. H x 8.35 in. L x 3.4 in./ 5 cm H x 21.1 cm L x 8.6 cm W	
Weight:	Scanner: ~8.4 oz./238 g; Cradle: ~6.4 oz./183 g	
Mounting Options:	Cradle supports vertical or horizontal positions	
Voltage & Current: (Cradle)	Voltage 5 +/-10% VDC 5 +/-10% VDC  12 +/-10% VDC 12 +/-10% VDC	Current (Charging / Non Charging) 620 mA / 70mA with external power 450 mA / 70mA with host power through cable 270 mA / 50mA with external power 230 mA / 50mA with host power through cable
Color:	Cash Register White (shown) or Twilight Black	

## Performance Characteristics

Light Source:	650 nm laser diode
Scan Element Frequency:	50Hz
Decode Rate:	200 decodes per second
Radio Range:	Minimum 33 ft./10 m; typical warehouse environment 50 ft./15 m
Battery Specifications:	720mAh NiMH - (3) AAA Number of scans per full charge: 32,000+ @ 1 scan/second Charge time: Fully discharged battery: < 3 hours via external power / ~4.5 hours via host power through cable Note: Typical daily scans are less than 4,000, which fully charges within 1 hour
Roll / Pitch / Yaw:	+/- 35° / 60° / 60°
Nominal Working Distance:	5 mil (Code 39): 1.5 to 5.5 in. (3.81 to 13.97 cm) 13 mil (100% UPC/EAN): 0 to 19 in. (0 to 48.25 cm) 10 mil (Code 39): 0 to 14 in. (0 to 35.56 cm) 20 mil (Code 39): 0 to 29 in. (0 to 73.66 cm)
Print Contrast:	25% minimum reflectance
Multi-Line Aiming Coverage:	At 5 in./12.7 cm reading distance: ~ 0.5 in./1.3 cm At 10 in./25.4 cm reading distance: ~ 1 in./2.5 cm
Motion Tolerances:	Horizontal velocity: 200 in./508 cm per second Vertical velocity: 200 in./508 cm per second Angular velocity: 200 in./508 cm per second

Decode Capability:	UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII, Tri-optic Code 39, RSS Variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code 93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5 MSI, Codell, IATA, Bookland EAN, Code 32
--------------------	--

Interfaces Supported:	LS4278 cradle features on-board multiple interface with: RS-232C (Standard, Nixdorf, ICL and Fujitsu); IBM 468x/469x; keyboard wedge; USB (Standard, IBM SurePOS, Macintosh); laser/wand emulation. In addition, Synapse adaptive connectivity allows for connectivity to all of the above plus many non-standard interfaces.
-----------------------	---

## User Environment

Operating Temperature:	32° to 122° F/0° to 50° C
Storage Temperature:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% non-condensing
Drop Specifications:	Withstands multiple 5 ft./1.5 m drops to concrete
# of Cradle Insertions:	250,000+ insertions
Ambient Light Immunity:	Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting conditions

## Regulatory

Electrical Safety:	UL1950, CSA C22.2 No. 950, EN60950/IEC950
Laser Safety:	CDRH Class II, IEC Class 2
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA
Radio:	Bluetooth, Class 2, Version 1.2, Serial Port & HID Profiles 2.402 to 2.480 GHz Adaptive Frequency Hopping (co-existence with 802.11 wireless networks) Data rate: 720 kbps

## Accessories

Brackets:	Desktop/wall-mount bracket
Power Supplies:	Power supplies are available for applications that do not supply power over the host cable

## Warranty

Subject to the terms of Symbol's hardware warranty statement, the LS 4278 handheld scanner products are warranted against defects in workmanship and materials for a period of three years from the date of shipment. The Liquid Polymer Scan Element includes an unprecedented limited lifetime warranty. For the complete Symbol hardware product warranty statement, go to: <http://www.symbol.com/warranty>.



LASER LIGHT- DO NOT STARE INTO BEAM . CLASS 2 LASER PRODUCT. LASERSTRAHLUNG - NICHT IN DEN STRAHL BLICKEN. LASER KLASSE 2. LUMIÈRE LASER - NE PAS REGARDER DANS LE FAISCEAU. APPAREIL À LASER DE CLASSE 2 630-680nm, 1mW

## About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs under the Symbol Enterprise Mobility Services brand. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at [www.symbol.com](http://www.symbol.com)

**symbol**  
The Enterprise Mobility Company™

Corporate Headquarters  
**Symbol Technologies, Inc.**  
One Symbol Plaza  
Holtville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

For Asia Pacific Area  
**Symbol Technologies Asia, Inc.**  
(Singapore Branch)  
Asia Pacific Division  
230 Victoria Street #12-06/10  
Bugis Junction Office Tower  
Singapore 188024  
TEL: +65.6796.9600  
FAX: +65.6796.7199

For Europe, Middle East and Africa  
**Symbol Technologies**  
EMEA Division  
Symbol Place, Winnersh Triangle  
Berkshire, England RG41 5TP  
TEL: +44.118.9457000  
FAX: +44.118.9457500

For North America, Latin America and Canada  
**Symbol Technologies**  
The Americas  
One Symbol Plaza  
Holtville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

**Symbol Website**  
For a complete list of Symbol subsidiaries and business partners worldwide contact us at:  
[www.symbol.com](http://www.symbol.com)  
**E-mail**  
[info@symbol.com](mailto:info@symbol.com)



DS-LS4278 12/05

Part No. DS-LS4278 Printed in USA 12/05 © Copyright 2005 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.